

Heat Capacitance Testing Device: Team #35

Steven Adams (EE), Tathagata Das (ME), Trevor Favrot (ME), Brooke Larsen (ME), Kenneth Lockett (ECE), Tommy Nguyen (ME)



Objective Statement

Design and construct an automatic heat capacitance testing device that requires little human interaction.

Background


Before hot tapping on process lines, a heat capacitance test is performed. This method requires operators to heat up the pipe surface with a blowtorch and monitor its cool-down with a temperature gun. This exposes a flame directly to a hydrocarbon-filled pipeline creating a potentially hazardous situation.

Phillips 66 has tasked Team #35 to design and build a prototype heat capacitance testing device to replace the current test.


Engineering Specifications

Goals/Constraints	
Weight	< 50 pounds
Volume	< 3 ft ³
Elbows	90°
Working Clearance	12"
Watt Density	Max Watt Density
Pipe Surface Temperature	500° F
Diameters	6"-24"
Piping Specification	Carbon Steel
Safety Requirements	Auto Shutoff
Operational Requirements	Clear Output
	Status Indicator
Budget	Constant Monitoring
	\$5,500

Budget



Predicted Cost: \$2,784
Total Project Cost: \$5,150.95
Remainder: \$349.05



(1) Type-K Thermocouple (2) Heating Apparatus (3) Electronic Housing

Embodiment

Two-part stainless steel 304L frame

- Carrying handles and polyesters straps for secure and easy mobility

Heating Mechanism

- Heating cartridges encased in carbon steel
- Individually linked casings for flexibility of pipe diameters
- Insulated for safety and optimum performance

Movement System

- Two stepper motors to raise and lower heating mechanism


Constant Monitoring System

- K-Type Thermocouple
- Electrical Components
- Arduino Due for control system

Safety

- Insulated heating mechanism
- Time and Temperature limit
- Automatic operation from start to finish
- Auto shut off for emergencies
- Easy and secure attachment
- Indicator lights providing updated device status
- Instruction and warning labels

Testing/Validation



The device reached the goal temperature of 500 °F and recorded the pipe surface cool down from 482-212 °F.

- Full Device Test**
- Set-up time: 1:50 minutes
 - Lowering System time: 4 second
 - Cool-Down Time: 65 seconds
- Testing Specifications:**
- 9 ft long 4" SCH 40 Carbon Steel Pipe
 - Water flowing at 3.75 GPM at 71 °F.




Testing Apparatus

Manufacturing



Carbon steel casing was drilled using a 0.25" drill bit and reamed using the lathe.




OMAX water jet used to cut 304 Stainless Steel for the device. Pressure 30+ ksi




Frame TIG welded using 308L filler material

Electrical Schematics



(1) Electronics circuit for the control system.



(2) Heating Cartridge circuit schematic.

